

Modem GSM/GPRS MODEM do rejestratorów Sxxxx, Rxxxx, Gxxxx

kod: LP040



Modem GSM/GPRS ze slotem karty SIM - bez akcesoriów.

Pozwala na pełną komunikację z rejestratorem przez GPRS - odczyt danych, konfiguracja. Rejestrator może być kontrolowany za pomocą wiadomości SMS wysyłanych z telefonu komórkowego.

Dane techniczne

| | |
|--------------------------------------|--|
| Communication with the device | RS232 (connector Canon 9) for the COM adapter |
| Frequency band | 850/900/1800/1900 MHz |
| Output power | Class 4 (+33dBm ±2dB) for EGSM850; Class 4 (+33dBm ±2dB) for EGSM900; Class 1 (+30dBm ±2dB) for GSM1800; Class 1 (+30dBm ±2dB) for GSM1900 |
| SIM card type | 1,8V or 3V |
| GPRS class | multislot class 12 |
| Antenna | 50 ohm, SMA connector |
| Supply terminal block | removable, WAGO 734, max. size of conductors 1.5 mm ² |
| IP code | IP30 |
| Power supply | external 9-32V DC, peak input up to 10W |
| Operating temperature range | from -30°C to +65°C |
| Operating position | arbitrary |
| Device mounting (optional equipment) | self-adhesive Dual Lock, wall holder, DIN rail holder |
| Storage conditions | temperature from -40°C to +85°C |
| Dimensions | 105 x 71 x 24mm (without antenna and holders) |
| Weight | cca 180g (without antenna and holders) |
| Box material | anodized aluminum |